



DC-直流轴流风扇 60x60x56mm

马达可选功能列表 (Available Functions)

1. 马达保护 (Moto protection)

AS

2. 信号输出 (Signal out put)

FG

RD


3. 调速方式 (Speed control mode)

PWM


TC



风扇P-Q曲线 / Fan performance curve



尺寸图 / DIMENSIONS DRAWING



Model		Bearing	Rated Voltage	Startup Voltage	Current	Power	Speed	Air Flow		Static Pressure		Noise
型号	功能	轴承	工作电压	启动电压	电流	功率	转速	风量	风量	风压	风压	噪音
Part NO.	Function	System	VDC	VDC	A	W	RPM	M ³ /min	CFM	mmH ₂ O	INH ₂ O	dBA
HDB0612UW	-A	Ball	12	6.0	5.70	68.40	IN:23000 OUT:20500	2.50	88.30	287.23	11.31	78.5
HDB0612HW	-A			6.0	4.26	51.12	IN:21000 OUT:18500	2.27	80.19	235.13	9.26	74.5
HDB0612MW	-A			6.0	2.95	35.40	IN:19000 OUT:16500	2.05	72.55	188.24	7.41	72.1
HDB0612LW	-A			6.0	2.10	25.20	IN:17000 OUT:14500	1.84	64.91	146.57	5.77	69.2
HDB0612UW	-A	Ball	24	12.0	3.00	72.00	IN:23000 OUT:20500	2.50	88.30	287.23	11.31	78.5
HDB0612HW	-A			12.0	2.13	51.12	IN:21000 OUT:18500	2.27	80.19	235.13	9.26	74.5
HDB0612MW	-A			12.0	1.48	35.52	IN:19000 OUT:16500	2.05	72.55	188.24	7.41	72.1
HDB0612LW	-A			12.0	1.05	25.20	IN:17000 OUT:14500	1.84	64.91	146.57	5.77	69.2